



# TYRE SEALANT DL-FVA

## SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 13.05.2022  
REVISION DATE: 07.05.2026  
SUPERSEDES: 31.08.2023  
VERSION: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Tyre Sealant DL-FVA  
Product code : Ford Internal Ref.: 506395  
SDS Number : 9510  
Unique Formula Identifier (UFI) : Q9F7-2F96-J106-6KKT  
Product use : Public use

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Function or use category : Adhesives, sealants

##### 1.2.2. Uses advised against

Restrictions on use : None known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Ford-Werke GmbH  
Edsel-Ford-Str. 2-14  
50769 Cologne  
Germany  
+49 221 90-33333  
sdseu@ford.com

##### Distributor

Ford Motor Company Ltd.  
Parts Distribution Centre  
Royal Oak Way South  
NN11 8NT Daventry, Northants  
United Kingdom  
+44 1327 305 198

#### 1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

<b>Health hazards</b>	Specific target organ toxicity – Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
-----------------------	--	------	--

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

#### Hazard pictograms



#### Signal word

Warning

#### Contains

Ethanediol

## Hazard statements

H373 May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements

### General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

### Prevention

P260 Do not breathe vapours.

### Response

P314 Get medical advice/attention if you feel unwell.

### Disposal

P501 Dispose of contents and container to an approved waste disposal plant.

EUH-statements EUH208 - Contains Natural rubber. May produce an allergic reaction.

## 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Natural rubber	9006-04-6 232-689-0	30 - < 50	Skin Sens. 1, H317	Exempted from REACH registration
Ethanediol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28-XXXX	20 - < 30	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg) STOT RE 2, H373	substance with a Community workplace exposure limit
ammonia	1336-21-6 215-647-6 007-001-01-2	0,25 - < 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1.0) Aquatic Chronic 2, H411	(5 ≤ C ≤ 100) STOT SE 3; H335 substance with a Community workplace exposure limit (Note B)

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash immediately with plenty of water. Get medical advice/attention if you feel unwell.
- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Do not induce vomiting. Rinse mouth thoroughly. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects: : May cause damage to organs through prolonged or repeated exposure.
- Symptoms/effects after skin contact : May produce an allergic reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO<sub>2</sub>).

#### 5.3. Advice for firefighters

- Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the MSDS.
- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up.

##### 6.1.2. For emergency responders

- Protective equipment : Wear recommended personal protective equipment. For personal protection, see section 8 of the SDS.
- Emergency procedures : Keep unnecessary personnel away. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak without risks if possible. Move containers from fire area if it can be done without personal risk.
- Methods for cleaning up : Take up liquid spill into absorbent material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water. Small spills: Stop leak without risks if possible. Wipe up with absorbent material (for example cloth). Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : " Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid release to the environment. Avoid contact with skin, eyes and clothing.
Hygiene measures	: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ensure adequate ventilation, especially in confined areas.
Storage conditions	: Store locked up. Store in a dry, cool and well-ventilated place.
Storage temperature	: > 15 °C

### 7.3. Specific end use(s)

Adhesives, Sealants.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

<b>Ethanediol (107-21-1)</b>
------------------------------

#### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Ethylene glycol
IOEL TWA	52 mg/m <sup>3</sup> 20 ppm
IOEL STEL	104 mg/m <sup>3</sup> 40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

#### United Kingdom - Occupational Exposure Limits

Local name	Ethane-1,2-diol
WEL TWA (OEL TWA)	10 mg/m <sup>3</sup> particulate 52 mg/m <sup>3</sup> vapour 20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m <sup>3</sup> vapour 40 ppm vapour
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

<b>ammonia (1336-21-6)</b>
----------------------------

#### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Ammonia, anhydrous
IOEL TWA	14 mg/m <sup>3</sup> 20 ppm
IOEL STEL	36 mg/m <sup>3</sup>

50 ppm

Regulatory reference

COMMISSION DIRECTIVE 2000/39/EC

### United Kingdom - Occupational Exposure Limits

---

Local name

Ammonia, anhydrous

WEL TWA (OEL TWA)

18 mg/m<sup>3</sup>

25 ppm

WEL STEL (OEL STEL)

25 mg/m<sup>3</sup>

35 ppm

Regulatory reference

EH40/2005 (Third edition, 2018). HSE

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

##### Ethanediol (107-21-1)

---

##### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal

106 mg/kg bodyweight/day

Long-term - local effects, inhalation

35 mg/m<sup>3</sup>

##### DNEL/DMEL (General population)

Long-term - systemic effects, dermal

53 mg/kg bodyweight/day

Long-term - local effects, inhalation

7 mg/m<sup>3</sup>

##### PNEC (Water)

PNEC aqua (freshwater)

10 mg/l

PNEC aqua (marine water)

1 mg/l

##### PNEC (Sediment)

PNEC sediment (freshwater)

37 mg/kg dwt

PNEC sediment (marine water)

3.7 mg/kg dwt

##### PNEC (Soil)

PNEC soil

1.53 mg/kg dwt

##### PNEC (STP)

PNEC sewage treatment plant

199.5 mg/l

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses with side shields. EN 166.

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing. Long sleeved protective clothing. EN 14605. EN ISO 13982

#### Hand protection:

protective gloves. DIN ISO 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see <a href="http://www.kcl.de">www.kcl.de</a> ) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see <a href="http://www.kcl.de">www.kcl.de</a> ) or comparable product.

#### Other skin protection

#### Materials for protective clothing:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Gas filters. A

### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Liquid.
Odour	: Ammoniacal.
Odour threshold	: Not available
Melting point	: -30 °C
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Not available
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 410 °C @ Ethanediol
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 9.5 (100%)
Viscosity, kinematic	: Not available
Solubility	: Miscible with water. Water: 100 g/l @ 20°C
Log Kow	: Not available

Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.01 g/cm <sup>3</sup> @ 20°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

### 9.2.2. Other safety characteristics

VOC content	: 0 %
Bulk density	: 1.02 kg/m <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Overheating.

### 10.5. Incompatible materials

Acids.

### 10.6. Hazardous decomposition products

During fire, gases hazardous to health may be formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Based on available data, the classification criteria are not met
Acute toxicity (dermal)	: Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met

<b>Tyre Sealant DL-FVA</b>	
ATE CLP (oral)	> 2000 mg/kg
<b>Ethanediol (107-21-1)</b>	
ATE CLP (oral)	500 mg/kg
<b>ammonia (1336-21-6)</b>	
LD50 oral rat	350 mg/kg

Skin corrosion/irritation	: Based on available data, the classification criteria are not met pH: 9.5 (100%)
Serious eye damage/irritation	: Based on available data, the classification criteria are not met pH: 9.5 (100%)

Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met (Skin sensitization (guinea pig): Not sensitizing [OECD 406])
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: Based on available data, the classification criteria are not met

#### ammonia (1336-21-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
------------------------	--

#### Ethanediol (107-21-1)

STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
------------------------	---

Aspiration hazard	: Based on available data, the classification criteria are not met
-------------------	--

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
--	--

### 11.2.2. Other information

Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye, Information on Effects: refer to section 4
-------------------	--

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Hazardous to the aquatic environment, short-term (acute)	: Based on available data, the classification criteria are not met
Hazardous to the aquatic environment, long-term (chronic)	: Based on available data, the classification criteria are not met

#### ammonia (1336-21-6)

LC50 - Fish [1]	0.89 mg/kg 96h; Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	101 mg/l 48 h; Daphnia magna (Water flea)
NOEC chronic fish	0.0135 mg/l 73 d; Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0.961 mg/l 21 d; Daphnia magna (Water flea)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### Ethanediol (107-21-1)

Log Pow	-1.36
---------	-------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### Tyre Sealant DL-FVA

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

## 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## 12.7. Other adverse effects

Other adverse effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation

: Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods

: Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not allow to enter drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.

European List of Waste (LoW, EC 2000/532)

: 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09  
15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Not regulated for transport

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(b)	Tyre Sealant DL-FVA ; Ethanediol ; ammonia
3(c)	ammonia

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : 0 %

Other information, restriction and prohibition regulations : Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.

##### Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes:

Section 2. Section 3. SECTION 4. SECTION 8. Section 9. SECTION 10. SECTION 11. SECTION 12. SECTION 13.

## Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
STEL	Short-term Exposure Limit
VOC	Volatile organic compounds
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
OEL	Occupational Exposure Limit
RRN	REACH Registration no.
TWA	Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour workday.

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

## Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Natural rubber. May produce an allergic reaction.

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

STOT RE 2	H373	Calculation method
-----------	------	--------------------

*The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.*

# Attachment to the Safety Data Sheet



Trade name: Tyre Sealant DL-FVA

Ford Internal Ref.: 506395

Revision Date: 07.05.2026

---

## Involved Products:

	<b>Finiscode</b>	<b>Part Number</b>	<b>Packaging</b>
1	2 744 867	VWN3CA 1568 BB	450 ml
2	2 897 115	VWN3CA 1568 BC	450 ml